

C06GQF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

C06GQF forms the complex conjugates of m Hermitian sequences, each containing n data values.

2 Specification

```
SUBROUTINE C06GQF(M, N, X, IFAIL)
  INTEGER          M, N, IFAIL
  real           X(M*N)
```

3 Description

This is a utility routine for use in conjunction with C06FPF and C06FQF to calculate inverse discrete Fourier transforms (see the Chapter Introduction).

4 References

None.

5 Parameters

- 1:** M — INTEGER *Input*
On entry: the number of Hermitian sequences to be conjugated, m .
Constraint: $M \geq 1$.
- 2:** N — INTEGER *Input*
On entry: the number of data values in each Hermitian sequence, n .
Constraint: $N \geq 1$.
- 3:** X(M*N) — *real* array *Input/Output*
On entry: the data must be stored in array X as if in a two-dimensional array of dimension (1:M,0:N-1); each of the m sequences is stored in a **row** of the array in Hermitian form. If the n data values z_j^p are written as $x_j^p + iy_j^p$, then for $0 \leq j \leq n/2$, x_j^p is contained in X(p, j), and for $1 \leq j \leq (n-1)/2$, y_j^p is contained in X($p, n-j$). (See also Section 2.1.2 of the Chapter Introduction.)
On exit: the imaginary parts y_j^p are negated. The real parts x_j^p are not referenced.
- 4:** IFAIL — INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

6 Error Indicators and Warnings

If on entry $IFAIL = 0$ or -1 , explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors detected by the routine:

$IFAIL = 1$

On entry, $M < 1$.

$IFAIL = 2$

On entry, $N < 1$.

7 Accuracy

Exact.

8 Further Comments

None.

9 Example

This program reads in sequences of real data values which are assumed to be Hermitian sequences of complex data stored in Hermitian form. The sequences are expanded into full complex form using C06GSF and printed. The sequences are then conjugated (using C06GQF) and the conjugated sequences are expanded into complex form using C06GSF and printed out.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      C06GQF Example Program Text
*      Mark 14 Revised.  NAG Copyright 1989.
*      .. Parameters ..
      INTEGER          MMAX, NMAX
      PARAMETER       (MMAX=5,NMAX=20)
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
*      .. Local Scalars ..
      INTEGER          I, IFAIL, J, M, N
*      .. Local Arrays ..
      real            U(MMAX*NMAX), V(MMAX*NMAX), X(MMAX*NMAX)
*      .. External Subroutines ..
      EXTERNAL        C06GQF, C06GSF
*      .. Executable Statements ..
      WRITE (NOUT,*) 'C06GQF Example Program Results'
*      Skip heading in data file
      READ (NIN,*)
20    READ (NIN,*,END=140) M, N
      IF (M.LE.MMAX .AND. N.LE.NMAX) THEN
          DO 40 J = 1, M
              READ (NIN,*) (X(I*M+J),I=0,N-1)
40    CONTINUE
      WRITE (NOUT,*)

```

```

        WRITE (NOUT,*) 'Original data values'
        WRITE (NOUT,*)
        DO 60 J = 1, M
            WRITE (NOUT,99999) '      ', (X(I*M+J),I=0,N-1)
60      CONTINUE
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Original data written in full complex form'
        IFAIL = 0
*
        CALL C06GSF(M,N,X,U,V,IFAIL)
*
        DO 80 J = 1, M
            WRITE (NOUT,*)
            WRITE (NOUT,99999) 'Real ', (U(I*M+J),I=0,N-1)
            WRITE (NOUT,99999) 'Imag ', (V(I*M+J),I=0,N-1)
80      CONTINUE
*
        CALL C06GQF(M,N,X,IFAIL)
*
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Conjugated data values'
        WRITE (NOUT,*)
        DO 100 J = 1, M
            WRITE (NOUT,99999) '      ', (X(I*M+J),I=0,N-1)
100     CONTINUE
*
        CALL C06GSF(M,N,X,U,V,IFAIL)
*
        WRITE (NOUT,*)
        WRITE (NOUT,*) 'Conjugated data written in full complex form'
*
        CALL C06GSF(M,N,X,U,V,IFAIL)
*
        DO 120 J = 1, M
            WRITE (NOUT,*)
            WRITE (NOUT,99999) 'Real ', (U(I*M+J),I=0,N-1)
            WRITE (NOUT,99999) 'Imag ', (V(I*M+J),I=0,N-1)
120     CONTINUE
        GO TO 20
    ELSE
        WRITE (NOUT,*) 'Invalid value of M or N'
    END IF
140 STOP
*
99999 FORMAT (1X,A,6F10.4)
END

```

9.2 Program Data

C06GQF Example Program Data

3	6					
0.3854	0.6772	0.1138	0.6751	0.6362	0.1424	
0.5417	0.2983	0.1181	0.7255	0.8638	0.8723	
0.9172	0.0644	0.6037	0.6430	0.0428	0.4815	

9.3 Program Results

C06GQF Example Program Results

Original data values

0.3854	0.6772	0.1138	0.6751	0.6362	0.1424
0.5417	0.2983	0.1181	0.7255	0.8638	0.8723
0.9172	0.0644	0.6037	0.6430	0.0428	0.4815

Original data written in full complex form

Real	0.3854	0.6772	0.1138	0.6751	0.1138	0.6772
Imag	0.0000	0.1424	0.6362	0.0000	-0.6362	-0.1424
Real	0.5417	0.2983	0.1181	0.7255	0.1181	0.2983
Imag	0.0000	0.8723	0.8638	0.0000	-0.8638	-0.8723
Real	0.9172	0.0644	0.6037	0.6430	0.6037	0.0644
Imag	0.0000	0.4815	0.0428	0.0000	-0.0428	-0.4815

Conjugated data values

0.3854	0.6772	0.1138	0.6751	-0.6362	-0.1424
0.5417	0.2983	0.1181	0.7255	-0.8638	-0.8723
0.9172	0.0644	0.6037	0.6430	-0.0428	-0.4815

Conjugated data written in full complex form

Real	0.3854	0.6772	0.1138	0.6751	0.1138	0.6772
Imag	0.0000	-0.1424	-0.6362	0.0000	0.6362	0.1424
Real	0.5417	0.2983	0.1181	0.7255	0.1181	0.2983
Imag	0.0000	-0.8723	-0.8638	0.0000	0.8638	0.8723
Real	0.9172	0.0644	0.6037	0.6430	0.6037	0.0644
Imag	0.0000	-0.4815	-0.0428	0.0000	0.0428	0.4815
