

## D03PVF – NAG Fortran Library Routine Document

**Note.** Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

### 1 Purpose

D03PVF calculates a numerical flux function using Osher's Approximate Riemann Solver for the Euler equations in conservative form. The routine is designed primarily for use with the upwind discretisation routines D03PFF, D03PLF or D03PSF, but may also be applicable to other conservative upwind schemes requiring numerical flux functions.

### 2 Specification

```

SUBROUTINE D03PVF(ULEFT, URIGHT, GAMMA, PATH, FLUX, IFAIL)
INTEGER          IFAIL
real          ULEFT(3), URIGHT(3), GAMMA, FLUX(3)
CHARACTER*1     PATH

```

### 3 Description

D03PVF calculates a numerical flux function at a single spatial point using Osher's Approximate Riemann Solver ([1], [2]) for the Euler equations (for a perfect gas) in conservative form. The user must supply the *left* and *right* solution values at the point where the numerical flux is required, i.e. the initial left and right states of the Riemann problem defined below. In the routines D03PFF, D03PLF and D03PSF, the left and right solution values are derived automatically from the solution values at adjacent spatial points and supplied to the subroutine argument NUMFLX from which the user may call D03PVF. The Euler equations for a perfect gas in conservative form are:

$$\frac{\partial U}{\partial t} + \frac{\partial F}{\partial x} = 0, \quad (1)$$

with

$$U = \begin{bmatrix} \rho \\ m \\ e \end{bmatrix} \quad \text{and} \quad F = \begin{bmatrix} m \\ \frac{m^2}{\rho} + (\gamma - 1) \left( e - \frac{m^2}{2\rho} \right) \\ \frac{me}{\rho} + \frac{m}{\rho}(\gamma - 1) \left( e - \frac{m^2}{2\rho} \right) \end{bmatrix}, \quad (2)$$

where  $\rho$  is the density,  $m$  is the momentum,  $e$  is the specific total energy, and  $\gamma$  is the (constant) ratio of specific heats. The pressure  $p$  is given by

$$p = (\gamma - 1) \left( e - \frac{\rho u^2}{2} \right), \quad (3)$$

where  $u = m/\rho$  is the velocity.

The routine calculates the Osher approximation to the numerical flux function  $F(U_L, U_R) = F(U^*(U_L, U_R))$ , where  $U = U_L$  and  $U = U_R$  are the left and right solution values, and  $U^*(U_L, U_R)$  is the intermediate state  $\omega(0)$  arising from the similarity solution  $U(y, t) = \omega(y/t)$  of the Riemann problem defined by

$$\frac{\partial U}{\partial t} + \frac{\partial F}{\partial y} = 0, \quad (4)$$

with  $U$  and  $F$  as in (2), and initial piecewise constant values  $U = U_L$  for  $y < 0$  and  $U = U_R$  for  $y > 0$ . The spatial domain is  $-\infty < y < \infty$ , where  $y = 0$  is the point at which the numerical flux is required. Osher's solver carries out an integration along a path in the phase space of  $U$  consisting of subpaths which are piecewise parallel to the eigenvectors of the Jacobian of the PDE system. There are two variants of the Osher solver termed O (original) and P (physical), which differ in the order in which the subpaths are taken. The P-variant is generally more efficient, but in some rare cases may fail (see [1] for details). The parameter PATH specifies which variant is to be used. The algorithm for Osher's solver for the Euler equations is given in detail in the Appendix of [2].

## 4 References

- [1] Hemker P W and Spekreijse S P (1986) Multiple grid and Osher's scheme for the efficient solution of the steady Euler equations *Applied Numerical Mathematics* **2** 475–493
- [2] Pennington S V and Berzins M (1994) New NAG Library software for first-order partial differential equations *ACM Trans. Math. Softw.* **20** 63–99
- [3] Quirk J J (1994) A contribution to the great Riemann solver debate *Internat. J. Numer. Methods Fluids* **18** 555–574

## 5 Parameters

- 1: ULEFT(3) — *real* array *Input*  
*On entry:* ULEFT( $i$ ) must contain the left value of the component  $U_i$  for  $i = 1, 2, 3$ . That is, ULEFT(1) must contain the left value of  $\rho$ , ULEFT(2) must contain the left value of  $m$  and ULEFT(3) must contain the left value of  $e$ .
- 2: URIGHT(3) — *real* array *Input*  
*On entry:* URIGHT( $i$ ) must contain the right value of the component  $U_i$  for  $i = 1, 2, 3$ . That is, URIGHT(1) must contain the right value of  $\rho$ , URIGHT(2) must contain the right value of  $m$  and URIGHT(3) must contain the right value of  $e$ .
- 3: GAMMA — *real* *Input*  
*On entry:* the ratio of specific heats  $\gamma$ .  
*Constraint:* GAMMA > 0.0.
- 4: PATH — CHARACTER\*1 *Input*  
*On entry:* the variant of the Osher scheme. The possible choices are 'O' (original) and 'P' (physical).  
*Constraint:* PATH = 'O' or 'P'.
- 5: FLUX(3) — *real* array *Output*  
*On exit:* FLUX( $i$ ) contains the numerical flux component  $\hat{F}_i$  for  $i = 1, 2, 3$ .
- 6: IFAIL — INTEGER *Input/Output*  
*On entry:* IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.  
*On exit:* IFAIL = 0 unless the routine detects an error (see Section 6).

**Note.** If the left and/or right values of  $\rho$  or  $p$  (from (3)) are found to be negative then the routine will terminate with an error exit (IFAIL = 2). If the routine is being called from the user-supplied subroutine NUMFLX in D03PFF etc., then a **soft fail** option (IFAIL = 1 or -1) is recommended so that a recalculation of the current time step can be forced using the IRES parameter.

## 6 Error Indicators and Warnings

Errors detected by the routine:

IFAIL = 1

On entry, GAMMA  $\leq$  0.0,  
 or PATH  $\neq$  'O' or 'P'.

IFAIL = 2

On entry, the left and/or right density or pressure value is less than 0.0.

## 7 Accuracy

The routine performs an exact calculation of the Osher numerical flux function, and so the result will be accurate to machine precision.

## 8 Further Comments

The routine must only be used to calculate the numerical flux for the Euler equations in exactly the form given by (2), with  $ULEFT(i)$  and  $URIGHT(i)$  containing the left and right values of  $\rho$ ,  $m$  and  $e$  for  $i = 1, 2, 3$  respectively. It should be noted that Osher's scheme, in common with all Riemann solvers, may be unsuitable for some problems (see Quirk [3] for examples). The time taken by the routine depends on the input parameter  $PATH$  and on the left and right solution values, since inclusion of each subpath depends on the signs of the eigenvalues. In general this cannot be determined in advance.

## 9 Example

See Example 2 in D03PLF.

---