

F11JQF – NAG Fortran Library Routine Document

Note. Before using this routine, please read the Users' Note for your implementation to check the interpretation of bold italicised terms and other implementation-dependent details.

1 Purpose

F11JQF solves a complex sparse Hermitian system of linear equations, represented in symmetric coordinate storage format, using a conjugate gradient or Lanczos method, with incomplete Cholesky preconditioning.

2 Specification

```

SUBROUTINE F11JQF(METHOD, N, NNZ, A, LA, IROW, ICOL, IPIV, ISTR,
1                B, TOL, MAXITN, X, RNORM, ITN, WORK, LWORK, IFAIL)
INTEGER          N, NNZ, LA, IROW(LA), ICOL(LA), IPIV(N),
1                ISTR(N+1), MAXITN, ITN, LWORK, IFAIL
  complex       A(LA), B(N), X(N), WORK(LWORK)
  real          TOL, RNORM
CHARACTER*(*)    METHOD

```

3 Description

This routine solves a complex sparse Hermitian linear system of equations:

$$Ax = b,$$

using a preconditioned conjugate gradient method [2], or a preconditioned Lanczos method based on the algorithm SYMMLQ [3]. The conjugate gradient method is more efficient if A is positive-definite, but may fail to converge for indefinite matrices. In this case the Lanczos method should be used instead. For further details see [1].

F11JQF uses the incomplete Cholesky factorization determined by F11JNF as the preconditioning matrix. A call to F11JQF must always be preceded by a call to F11JNF. Alternative preconditioners for the same storage scheme are available by calling F11JSF.

The matrix A and the preconditioning matrix M are represented in symmetric coordinate storage (SCS) format (see Section 2.1.2 of the Chapter Introduction) in the arrays A , $IROW$ and $ICOL$, as returned from F11JNF. The array A holds the non-zero entries in the lower triangular parts of these matrices, while $IROW$ and $ICOL$ hold the corresponding row and column indices.

4 References

- [1] Barrett R, Berry M, Chan T F, Demmel J, Donato J, Dongarra J, Eijkhout V, Pozo R, Romine C and van der Vorst H (1994) *Templates for the Solution of Linear Systems: Building Blocks for Iterative Methods* SIAM, Philadelphia
- [2] Meijerink J and van der Vorst H (1977) An iterative solution method for linear systems of which the coefficient matrix is a symmetric M-matrix *Math. Comput.* **31** 148–162
- [3] Paige C C and Saunders M A (1975) Solution of sparse indefinite systems of linear equations *SIAM J. Numer. Anal.* **12** 617–629

5 Parameters

- 1:** METHOD — CHARACTER*(*) *Input*
On entry: specifies the iterative method to be used. The possible choices are:
- 'CG' Conjugate Gradient method;
'SYMLQ' Lanczos method (SYMLQ).
- Constraint:* METHOD = 'CG' or 'SYMLQ'.
- 2:** N — INTEGER *Input*
On entry: n , the order of the matrix A . This **must** be the same value as was supplied in the preceding call to F11JNF.
Constraint: $N \geq 1$.
- 3:** NNZ — INTEGER *Input*
On entry: the number of non-zero elements in the lower triangular part of the matrix A . This **must** be the same value as was supplied in the preceding call to F11JNF.
Constraint: $1 \leq \text{NNZ} \leq N \times (N+1)/2$.
- 4:** A(LA) — **complex** array *Input*
On entry: the values returned in array A by a previous call to F11JNF.
- 5:** LA — INTEGER *Input*
On entry: the dimension of the arrays A, IROW and ICOL as declared in the (sub)program from which F11JQF is called. This **must** be the same value as was supplied in the preceding call to F11JNF.
Constraint: $\text{LA} \geq 2 \times \text{NNZ}$.
- 6:** IROW(LA) — INTEGER array *Input*
7: ICOL(LA) — INTEGER array *Input*
8: IPIV(N) — INTEGER array *Input*
9: ISTR(N+1) — INTEGER array *Input*
On entry: the values returned in arrays IROW, ICOL, IPIV and ISTR by a previous call to F11JNF.
- 10:** B(N) — **complex** array *Input*
On entry: the right-hand side vector b .
- 11:** TOL — **real** *Input*
On entry: the required tolerance. Let x_k denote the approximate solution at iteration k , and r_k the corresponding residual. The algorithm is considered to have converged at iteration k if:
- $$\|r_k\|_\infty \leq \tau \times (\|b\|_\infty + \|A\|_\infty \|x_k\|_\infty).$$
- If $\text{TOL} \leq 0.0$, $\tau = \max(\sqrt{\epsilon}, \sqrt{n}\epsilon)$ is used, where ϵ is the **machine precision**. Otherwise $\tau = \max(\text{TOL}, 10\epsilon, \sqrt{n}\epsilon)$ is used.
Constraint: $\text{TOL} < 1.0$.
- 12:** MAXITN — INTEGER *Input*
On entry: the maximum number of iterations allowed.
Constraint: $\text{MAXITN} \geq 1$.

- 13:** X(N) — *complex* array *Input/Output*
On entry: an initial approximation to the solution vector x .
On exit: an improved approximation to the solution vector x .
- 14:** RNORM — *real* *Output*
On exit: the final value of the residual norm $\|r_k\|_\infty$, where k is the output value of ITN.
- 15:** ITN — INTEGER *Output*
On exit: the number of iterations carried out.
- 16:** WORK(LWORK) — *complex* array *Workspace*
17: LWORK — INTEGER *Input*
On entry: the dimension of the array WORK as declared in the (sub)program from which F11JQF is called.
- Constraints:*
- if METHOD = 'CG', LWORK $\geq 6 \times N + 120$;
 - if METHOD = 'SYMMLQ', LWORK $\geq 7 \times N + 120$.
- 18:** IFAIL — INTEGER *Input/Output*
On entry: IFAIL must be set to 0, -1 or 1. For users not familiar with this parameter (described in Chapter P01) the recommended value is 0.
On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

6 Errors and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors detected by the routine:

IFAIL = 1

- On entry, METHOD \neq 'CG' or 'SYMMLQ',
 - or $N < 1$,
 - or $NNZ < 1$,
 - or $NNZ > N \times (N+1)/2$,
 - or LA too small,
 - or $TOL \geq 1.0$,
 - or $MAXITN < 1$,
 - or LWORK too small.

IFAIL = 2

- On entry, the SCS representation of A is invalid. Further details are given in the error message. Check that the call to F11JQF has been preceded by a valid call to F11JNF, and that the arrays A, IROW and ICOL have not been corrupted between the two calls.

IFAIL = 3

- On entry, the SCS representation of M is invalid. Further details are given in the error message. Check that the call to F11JQF has been preceded by a valid call to F11JNF, and that the arrays A, IROW, ICOL, IPIV and ISTR have not been corrupted between the two calls.

IFAIL = 4

The required accuracy could not be obtained. However, a reasonable accuracy has been obtained and further iterations could not improve the result.

IFAIL = 5

Required accuracy not obtained in MAXITN iterations.

IFAIL = 6

The preconditioner appears not to be positive-definite.

IFAIL = 7

The matrix of the coefficients appears not to be positive-definite (conjugate gradient method only).

IFAIL = 8

A serious error has occurred in an internal call to an auxiliary routine. Check all subroutine calls and array sizes. Seek expert help.

7 Accuracy

On successful termination, the final residual $r_k = b - Ax_k$, where $k = \text{ITN}$, satisfies the termination criterion

$$\|r_k\|_\infty \leq \tau \times (\|b\|_\infty + \|A\|_\infty \|x_k\|_\infty).$$

The value of the final residual norm is returned in RNORM.

8 Further Comments

The time taken by F11JQF for each iteration is roughly proportional to the value of NNZC returned from the preceding call to F11JNF. One iteration with the Lanczos method (SYMMLQ) requires a slightly larger number of operations than one iteration with the conjugate gradient method.

The number of iterations required to achieve a prescribed accuracy cannot easily be determined a priori, as it can depend dramatically on the conditioning and spectrum of the preconditioned matrix of the coefficients $\bar{A} = M^{-1}A$.

9 Example

This example program solves a complex sparse Hermitian positive-definite system of equations using the conjugate gradient method, with incomplete Cholesky preconditioning.

9.1 Program Text

Note. The listing of the example program presented below uses bold italicised terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```

*      F11JQF Example Program Text.
*      Mark 19 Release. NAG Copyright 1999.
*      .. Parameters ..
      INTEGER          NIN, NOUT
      PARAMETER       (NIN=5,NOUT=6)
      INTEGER          NMAX, LA, LIWORK, LWORK
      PARAMETER       (NMAX=1000,LA=10000,LIWORK=2*LA+7*NMAX+1,
+                    LWORK=7*NMAX+120)
*      .. Local Scalars ..
      real            DSCALE, DTOL, RNORM, TOL
      INTEGER          I, IFAIL, ITN, LFILL, MAXITN, N, NNZ, NNZC, NPIVM
      CHARACTER       MIC, PSTRAT

```

```

CHARACTER*6      METHOD
*   .. Local Arrays ..
complex       A(LA), B(NMAX), WORK(LWORK), X(NMAX)
INTEGER         ICOL(LA), IPIV(NMAX), IROW(LA), ISTR(NMAX+1),
+              IWORK(LIWORK)
*   .. External Subroutines ..
EXTERNAL        F11JNF, F11JQF
*   .. Executable Statements ..
WRITE (NOUT,*) 'F11JQF Example Program Results'
*   Skip heading in data file
READ (NIN,*)

*
*   Read algorithmic parameters
*
READ (NIN,*) N
IF (N.LE.NMAX) THEN
  READ (NIN,*) NNZ
  READ (NIN,*) METHOD
  READ (NIN,*) LFILL, DTOL
  READ (NIN,*) MIC, DSCALE
  READ (NIN,*) PSTRAT
  READ (NIN,*) TOL, MAXITN

*
*   Read the matrix A
*
DO 20 I = 1, NNZ
  READ (NIN,*) A(I), IROW(I), ICOL(I)
20 CONTINUE

*
*   Read rhs vector b and initial approximate solution x
*
READ (NIN,*) (B(I),I=1,N)
READ (NIN,*) (X(I),I=1,N)

*
*   Calculate incomplete Cholesky factorization
*
IFAIL = 0
CALL F11JNF(N,NNZ,A,LA,IROW,ICOL,LFILL,DTOL,MIC,DSCALE,PSTRAT,
+          IPIV,ISTR,NNZC,NPIVM,IWORK,LIWORK,IFAIL)

*
*   Solve Ax = b using F11JQF
*
CALL F11JQF(METHOD,N,NNZ,A,LA,IROW,ICOL,IPIV,ISTR,B,TOL,MAXITN,
+          X,RNORM,ITN,WORK,LWORK,IFAIL)

*
WRITE (NOUT,99999) 'Converged in', ITN, ' iterations'
WRITE (NOUT,99998) 'Final residual norm =', RNORM

*
*   Output x
*
DO 40 I = 1, N
  WRITE (NOUT,99997) X(I)
40 CONTINUE
END IF
STOP

*
99999 FORMAT (1X,A,I10,A)
99998 FORMAT (1X,A,1P,e16.3)

```

```
99997 FORMAT (1X,'(',e16.4,',',e16.4,')')
END
```

9.2 Program Data

F11JQF Example Program Data

```

9          N
23        NNZ
'CG'      METHOD
0 0.0     LFILL, DTOL
'N' 0.0   MIC, DSCALE
'M'       PSTRAT
1.0E-6 100 TOL, MAXITN

( 6., 0.) 1 1
(-1., 1.) 2 1
( 6., 0.) 2 2
( 0., 1.) 3 2
( 5., 0.) 3 3
( 5., 0.) 4 4
( 2.,-2.) 5 1
( 4., 0.) 5 5
( 1., 1.) 6 3
( 2., 0.) 6 4
( 6., 0.) 6 6
(-4., 3.) 7 2
( 0., 1.) 7 5
(-1., 0.) 7 6
( 6., 0.) 7 7
(-1.,-1.) 8 4
( 0.,-1.) 8 6
( 9., 0.) 8 8
( 1., 3.) 9 1
( 1., 2.) 9 5
(-1., 0.) 9 6
( 1., 4.) 9 8
( 9., 0.) 9 9      A(I), IROW(I), ICOL(I), I=1,...,NNZ
( 8., 54.)
(-10., -92.)
( 25., 27.)
( 26., -28.)
( 54., 12.)
( 26., -22.)
( 47., 65.)
( 71., -57.)
( 60., 70.)      B(I), I=1,...,N
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)
( 0., 0.)      X(I), I=1,...,N

```

9.3 Program Results

F11JQF Example Program Results

Converged in 5 iterations

Final residual norm = 3.197E-14

```
( 0.1000E+01, 0.9000E+01)
( 0.2000E+01, -0.8000E+01)
( 0.3000E+01, 0.7000E+01)
( 0.4000E+01, -0.6000E+01)
( 0.5000E+01, 0.5000E+01)
( 0.6000E+01, -0.4000E+01)
( 0.7000E+01, 0.3000E+01)
( 0.8000E+01, -0.2000E+01)
( 0.9000E+01, 0.1000E+01)
```
